

MH Range | undercounter



MH520



MH520T



MH720

- 2 year warranty
- Soft touch control fascia
- Twin LED digital temperature display
- All models double skinned for minimum heat loss and maximum noise reduction
- All models with fitted breaktank
- Wash tank designed to reduce water consumption and ease cleaning
- Three cycle options which can be programmed to match sites requirements to run between 25 and 300 seconds
- Self-draining wash pump on all models
- Standard with both detergent and rinse aid dosing
- All models supplied with one open/cup and one plate rack
- **MH520T gives the ability to wash plates of up to 380mm diameter; this model is only suitable for gravity drain, it is not possible to fit a drain pump on this model**
- MH720 upright model takes the biggest plates up to 430mm diameter
- **MH720 supplied with open ended tray rack**
- MH520 & MH720 supplied with surface scrap trays

Technical

- Standard voltage 240V – single phase
- All models can be supplied for 3 phase
- Suitable for hot (max 50°C) or cold* water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 55°C (adjustable)
- Rinse temperature 85°C (adjustable)
- Cycle times between 25 & 300 secs, dependent on model

*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required	Price
MH520	500	320	600 x 640 x 820 [#]	3 Cycles	5.6	25	
MH520T	500	380	600 x 680 x 850 [#]	3 Cycles	5.6	25	
MH720	500	430	600 x 700 x 1250 [#]	3 Cycles	7.7	32	
HALDP4	Additional charge for fitted drain pump on MH520 and MH720 models only (also available as retro fitted kit)						

Height excludes feet which will add 15mm, MH720 legs add 135 to 210mm.

It is strongly recommended that 500mm machines are installed on hot water fill (max 50°C) for optimum performance.