



AMH51

AMH55 WSD



AMH80,
AMH91 &
AMH95 WSD
(AMH91 model
shown with soft
touch controls)



- 1 year warranty
- **NEW** increased useable height on all models
- **NEW** three button bright LED display with soft touch controls and alarms menu on all models
- **NEW** accurate detergent and rinse aid peristaltic dosing pumps with dosing setup by fascia controls on all models
- **NEW** composite easy clean parallel wash and rinse arm assembly on all models
- AMH51, AMH55 WSD, AMH91 & AMH95 WSD supplied with internal breaktank as standard
- AMH55 WSD & AMH95 WSD with internal automatic water softener & drain pump as standard
- Drain pump version available on AMH51*, AMH80 & AMH91
- Composite surface scrap trays supplied as standard on AMH91 & AMH95 WSD, optional on all other models
- All models supplied with one pegged plate rack, one open cup/glass rack and cutlery insert

Technical

- Standard voltage 230V – single phase
- All models can be supplied for 3 phase operation – please specify at time of order
- Suitable for hot (max 50°C) or cold water supply, typically at 2 to 4 bar dynamic supply pressure, refer to specification sheets for individual requirements
- Wash temperature 60°C – adjustable
- Rinse temperature 82°C – adjustable

* Drain pump cannot be retro fitted to AMH51.

Drain pump versions require a waste up stand for correct operation. Restrictive waste connections should be avoided for all installations. All machines supplied 13 amp will come with molded plug and cable. Machines configured for 13 amp supply or fitted to cold water supply will not be capable of running repeated short cycles. The cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Time Sec	Power kW	Amps Required
AMH51*	500	340	580 x 610 x 810 [#]	90/180	2.6/4.5/6.5	13/20/30 ^{###}
AMH51 D	As AMH51 above with fitted drain pump					
AMH55 WSD	500	340	580 x 610 x 810 [#]	90/180	2.6/4.5/6.5	13/20/30 ^{###}
	AMH55 WSD supplied with drain pump as standard					
AMH80	500	435	640 x 745 x 1500 [#]	90/180	4.5/6.5	20/30 ^{###}
AMH80 D	As AMH80 above with fitted drain pump					
AMH91	500	435	640 x 745 x 1500 [#]	90/180	4.5/6.5	20/30 ^{###}
AMH91 D	As AMH91 above with fitted drain pump					
AMH95 WSD	500	435	640 x 745 x 1500 [#]	90/180	4.5/6.5	20/30 ^{###}
	AMH95 WSD supplied with fitted drain pump as standard					

Height excludes feet which add 10 to 20mm.

Height adjustable from 1500 to 1560mm (hood closed), 1980 to 2040mm (hood open). Height includes adjustable legs.

Machines will be supplied for 30 amp supply as standard, if 20 amp required specify at time of order. If supplied 13 amp machine will come fitted with molded plug and cable. 20 amp machines will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

It is strongly recommended that for busy sites to achieve optimum performance that machines are installed on hot fill (max 50°C).