BLUE SEAL EVOLUTION SERIES®

Technical data sheet for

GAS RANGE STATIC OVEN 900mm

G506D, G506C, G506B, G506A



- 7kW open burners
- Flame failure standard
- Pilot burners optional
- 300mm, 600mm, and 900mm griddle plate options
- Optional simmer plates
- GN 2/1 gas static oven
- Drop down door
- Rear rollers
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular

Overall Construction

- Galvanized steel chassis
- Welded hob with 1.5mm stainless steel bull nose
- Hob sides 1.2mm stainless steel
- Splashback 1.2mm stainless steel
- Front panels and oven sides 0.9mm stainless steel
- Enamelled hob control panel
- 63mm dia. heavy-duty 1.2mm stainless steel adjustable legs at front and two rollers at rear

Cooktop

- Cast iron 7kW open burners with forged brass cap
- Enamelled cast iron potstands
- Enamelled open burner spill covers
- Cast iron simmer plates (optional extra)
- \bullet 12mm thick mild steel griddle plates
- 2.5mm stainless steel griddle splash guards
- Stainless steel spill trays
- Aluminised steel internal construction

Griddle sections are standard on RH side. Available on LH side or centre to order or by conversion.

Oven

- Fully welded and enamelled oven liner
- GN 2/1 capacity with 4 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Cast iron even heat oven sole plate
- 9kW oven burner
- Pilot and flame failure with piezo ignition
- Drop down door
- 0.9mm stainless steel door outer
- 1.0mm enamelled door inner
- High density fibreglass insulated
- Supplied with two chrome wire oven racks



Controls

- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

Cooktop

- Variable high to low controls to open burners
- Open burners flame failure standard with pilot burners optional
- Variable high to low controls to griddles
- Griddles standard with pilot, flame failure and piezo ignition

Oven

- 80-300°C thermostatic control
- Piezo ignition to pilot burner
- Flame failure

Cleaning and Servicing

- \bullet All models with easy clean stainless steel external finish
- Lift off burner heads and enamelled burner spill covers
- Stainless steel spill trays under open burner and griddle sections
- Bottom sill removable for oven burner and pilot access
- Removable oven racking and sole plate
- Easy clean enamelled oven and door inner
- \bullet Access to all parts from front of unit

Technical data sheet for

GAS RANGE STATIC OVEN 900mm

OBLUE SEAL

Specifications

Burners

Open Burners 7kW dual flame ring with simmer rate
Griddle Burners 6kW per 300mm section

Griddle Burners 6kW per 300mm section Oven 9kW tubular under cast iron sole plate

Gas power (gross)

G506D 51kW, 174,300 Btu/hr G506C 43kW, 146,500 Btu/hr G506B 35kW, 119,000 Btu/hr G506A 27kW, 91,000 Btu/hr

Griddle Plate

300mm Griddle cooking surface 292mm x 475mm, 1387cm2 600mm Griddle cooking surface 592mm x 475mm, 2812cm2 900mm Griddle cooking surface 892mm x 475mm, 4237cm2

Oven Dimensions

Width 665mm Depth 590mm Height 385mm Rack size 660mm x 540mm Rack positions 4

Gas connection

R ³/₄ (BSP) male Optional underside connection, please specify when ordering All units supplied with Natural and LP gas regulator

Dimensions

Width 900mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight

215kg

Packing data

1.03m3, 280kg Width 945mm Depth 870mm Height 1255mm


Gas types

Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits

Options

Adjustable feet at rear Simmer plates (replaces Potstand) Ribbed griddle plates Joining caps Castors


G506



G506D



G506C



G506B



G506A



Supplied By
KiD Catering Equipment
Oaktree Court Business Centre
Mill Lane, Ness, Cheshire, CH64 8TP
Tel: 0333 123 2450
sales@kidcateringequipment.com



ISO9001 Quality Management Standard

Designed and manufactured by

MOFFAT.

IS09001

All Blue Seal products are designed and manufactured by Moffat using the internationally recognised IS09001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

CE

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.



