

Savant

Blue Seal Electric Combi Steamer **SAVANT** E10SBW 10 x 1/1 GN



- Manual controls
- Boiler system
- Multi-point core temperature probe
- High visibility display
- Two speed fan
- 90 preset recipe programs
- 99 free programs with 4 cycles, automatic sequence
- Multiprogram keypad for quick, "press and go" program selection with nine positions
- Electronic thermostat 30° 300°C
- Auto-reversing fan rotation
- Autoclima with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Built-in retractable hand shower with tap
- SCS (Solid Clean System) automatic cleaning system with built in tank and automatic detergent dispenser
- CALOUT descaling system that prevents formation and accumulation of limescale in the boiler, with builtin tank and automatic dispensing
- 4 LED's to indicate actual cooking cycle in programme mode
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- USB connection

- INCOLOY 800 type heating elements
- AISI 304 fully insulated steam generator
- Automatic boiler pre-heating
- Daily automatic boiler draining and rinsing
- Stainless steel construction
- Perfectly smooth, water tight chamber
- Adjustable door hinge for optimal seal
- Halogen oven light

GENERAL FEATURES

- Oven door handle mechanism allows either left or right operation
- Cool to touch door with double tempered glass with air chamber and interior heat-reflective glass

- Hinged inner glass for easy cleaning
- Constant self-diagnosis for error recognition
- IPX5 spray-proof and hose proof.
- Rack runners for GN loading

OPTIONAL FEATURES

- Right hinged door
- Side runners for 600 x 400 trays
- Configuration for connection to extraction hood













SOLID CLEAN

SOLID CAL

AUTOCLIM

FAST-DRY



Savant

Blue Seal Electric Combi Steamer **SAVANT** E10SBW 10 x 1/1 GN

Dimensions

Width 930mm Depth 825mm Height 1040mm Weight 174kg

Packed Dimensions

Width 1040mm Depth 980mm Height 1250mm Weight 197kg

Shelves

1/1 GN 10 Shelf Spacings 70mm

Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

Supply line voltage

400-415V ~ 50Hz, 3P+N+E

Special voltage options available on request.

Power Connection

Total (kW) 16 Convection power (kW) 15 Steam power (kW) 15 Rated Current (A) (400V) 23

Installation clearances

- rear 25mm - right 500mm* - left 50mm
- *Clearance required on fixed installations for service accessibility.


If heat sources are located near the RH side of the Savant combi, ensure that a minimum distance of 400mm is maintained.


Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.


Water connection requirements

- cold water
- flow pressure (200-500kPa)
- soft water connection*
- shut-off valve with return flow inhibitor and dirt filter
- water supply R3/4
- R50 waste water connection

(*Water softener may be required. Please refer to installation manual for water treatment values.)











Air extraction



Softened water



Steam vent and chamber pressure drop safety device

Electric power supply cable inlet



Normal water



Liquid outlet

Distributor: KiD Catering Equipment Oaktree Court Business Centre Mill Lane, Ness Cheshire, CH64 8TP Tel: 0333 123 2450 sales@kidcateringequipment.com

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd UK.BSS.S.1401



