

CS3000GB 2 x 3kW Table-top twin Product Specifications



Maximum Power	7kW
Electrical Supply	415V AC 50Hz 32-amp 3-phase + N&E; 32-amp single phase; or 230V 2 x 13-amp (to be specified at time of order).
Cord & Plug	Cord length 1.8m 5-pin 32-amp Commando plug fitted or 3-core 32 amp cable (hardwired, or 32-amp 3 pin plug), 32-amp single phase (UK) or 2 x 13 amp mains leads Appropriate plug for each export market
Weight	30kg
Dimensions (mm)	W: 435 L: 720 H: 163
Construction	Ceran top, stainless steel casing
Depth of Field	Up to 30mm
Safety Features	Pan detection; boil-dry protection; overheat prevention; clean filter warning
User Interface	Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown
Controls	2 x Ergonomically designed knobs with precise settings of 1 through 99
Installation	Installation instructions provided
Cooling Clearance	Rear to front ventilation - integral overhang at rear, with easily removed filter
Bespoke Options	Ceran top design - minimum quantity 50
Warranty	2 years parts and labour, excluding case, Ceran top
CE	Approved

Induced Energy Limited operates a continuous programme of product development and improvement. Product specifications may therefore be subject to change.