

Features

E6 0D

MOTOR 610 W TO 1290 RPM

Powerful Motor that allows you to work continuously in situations of high demand, maintaining all the properties of the coffee thanks to the cold grinding at low revolutions.



P-K K-6889

FLAT 64 MM BURRS

Ensures accurate particle size for Espresso and spectacular productivity: 7 gr in 2.1 seconds. Special pre-wear treatment is applied to ensure optimal performance from the first use. Durability of 500 Kg.

LCD DISPLAY

Multilanguage
Changing burrs alarm
3 Modes: Pre-selection - Automatic - Instant
Refill Button
Absolute and relative coffees counting
Activate pad and end of service sound
Password





CONTINUOUS MICROMETRIC ADJUSTMENT SYSTEM PARALLEL

Set the grind point with maximum precision in a very simple and intuitive way. The new Parallel locking system provides an extra level of security ensuring parallel positioning between burrs at all times.



ACCURATE DOSING. TIME PER Dose: 1.9 Sec. = 7 GR Espresso (*)

(*) Calculated time to the grind point for a cup of Espresso coffee 25 ml in 25 seconds. With 7 grams of coffee.



ADJUSTABLE PORTA-FORK HEIGHT, UNIVERSAL CLAMP AND HOLDER

Perfect fit for the most common portafilter sizes, which also allows for hands-free usage.



THREE POSITION SWITCH

Offers total control to the Barista without been necessary to use the electronical system of the grinder.



ELECTRICAL COMPONENTS CERTIFICATE

According to Directive 2011/65/EU.

© 2014 Compak. All rights reserved