

C Range | undercounter

Distributor:

KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
Tel: 0333 123 2450 sales@kidcateringequipment.com



C352

C402

C452

C501 & C515 WSD

- 2 year warranty
- **NEW** Dual flow wash pump on C402 and C452
- **NEW** Parallel quick release wash & rinse arm design on C352, C402 and C452
- **NEW** Surface scrap tray filters supplied as standard on ALL models
- **NEW** Alarms menu on C352, C402 and C452
- **NEW** Molded wash tank for easy cleaning on C352, C402 and C452
- **NEW** molded rack guide on C352 and C402 giving partial double skin
- All C500 type models are partial double skinned reducing noise and heat loss
- C515 WSD with automatic water softener, break tank and drain pump as standard and supplied with one pegged and one open rack
- C352, C402, C452 and C501 supplied with two open cup/glass racks
- C515 WSD supplied with one pegged and one open cup/glass rack
- Drain pump available on all models
- Accurate detergent and rinse aid peristaltic dosing as standard
- Three standard cycle time options with further options available on ALL models
- Cycle times can be tailored to site requirements
- Selectable energy saving mode
- Automatic self-cleaning at end of service
- Selectable thermostat ensures optimum rinse temperatures
- Operational self-diagnostics
- Bright LED display with soft touch controls
- Twin traffic light display indicates machine status



C352, C402 & C452 only



C501 & C515 WSD only

Technical

- Standard voltage 240V – single phase
- 500mm rack models can be supplied for 3 phase
- Suitable for hot (max 50°C) or cold water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 60°C (adjustable)*
- Rinse temperature 65°C (adjustable)*
- Cycle times between 70 & 240 secs, dependent on model

*Not including C515 WSD, please see page 7.

Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
C352	350	240	400 x 495 x 590 [†]	3 Cycles	2.9	13
C352D			As C352 above with fitted drain pump			
C402	390	300	440 x 540 x 665 [†]	3 Cycles	2.8	13
C402D			As C402 above with fitted drain pump			
C452	450	280	525 x 560 x 705 [†]	3 Cycles	2.9	13
C452D			As C452 above with fitted drain pump			
C501	500	320	580 x 610 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}
C501D			As C501 above with fitted drain pump			
C515 WSD	500	320	580 x 610 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}

[†] Height excludes adjustable feet which will add 5 to 15mm. [#] Height excludes adjustable feet which will add 10 to 20mm.

^{##} Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

See page 10 for ancillary items.