



## DYNAMIC PREPARATION

VACUUM PACKING MACHINES



# Vacuum packing machine SV-204T

#### **COMPACT TABLE TOP UNIT**

#### 264 mm sealing bar length.

- · Improves the durability of cooked or raw food, with no loss of weight.
- · Electronic timer controlling the vacuum process and the sealing of the pack to match the preset time.
- · Stainless steel body.
- · Stainless steel deep-drawn chamber.
- · Cordless sealing bar.
- · Softair as standard.
- · Digital keyboard.
- · LED's indicate each cycle stage whilst performing.
- · STOP key allows the interruption of the cycle at any stage, moving on to the next
- · Pump drying program: improves the durability of the machine.
- · Working hours counter display, which allows to know when oil must be replaced.
- · NSF-International certified appliance (complying with Hygiene, Cleaning and Food Material regulations).

#### **TECHNICAL SPECIFICATIONS**

Pump capacity: 4 m3/h

Useful length of the sealing bar: 264 mm

Loading: 100 W

Vacuum pressure (maximum): 2 mbar

#### Internal dimensions

- ·internal dimensions width: 280 mm
- ·internal dimensions depth: 300 mm
- ·internal dimensions height: 90 mm

### External dimensions

·Width: 323 mm ·Depth: 405 mm ·Height: 260 mm

Net weight: 23 Kg

DEFAULT EQUIPMENT Insert plate set

OPTIONAL EQUIPMENT

Vac-Norm external vacuum kit

Bag cutting kit
Liquid insert plate set









SAMMIC, S.L. (Sociedad Unipers irte, 1 - 20720 AZKOITIA - www.sa

2006/42/EC, 2006/95/EC, 2004/108/EC

UNE-EN 60335-1, UNE-EN 60335-2-64, EN 55014-1, EN 55014-2, EN 61000-3-2, NSF/ANSI Estándar 169.