

iPlate

Swanstone or Ceran Induction Keep Hot (Drop-in version)

Product Specifications



Surface Footprint	730 x 620mm -to accept 2 x 1/1 GN containers or modules thereof. Other Induction friendly containers can be used.	
Maximum Power	1.8 kW	
Electrical Supply	13amp single phase 210-265 volts 50or 60Hz Max load 5 amps	
Cord & Plug	Power Cord length 1.8m, Control Box to Coil Box 1.6m 3 pin 13amp single phase (UK) plug fitted as standard	
Weight kg	Coil Box 8.4 Control Box 3.9 Ceran 6.9 Swanstone top xxxx	
Dimensions (mm)	Drop-in Coil Box	W:733 L: 615 H:95
	Control Box	W:130 L:280 H:280
	Ceran Footprint	W:730 x L:620
	Counter aperture	W: 710 x L:595
	Rebate	15
	Rebate depth	9
Construction	Coil Box	Ceran/Swanstone top, steel casing
	Control Box	Aluminium or Steel casing
User Interface Display panel:	Green & Red LED's	
Controls	Control Box - 1 Power on/off switch, 6 stage rotary power setting, LED indication of power on/off and system running.	
Installation	Installation instructions provided. Only to be installed by an installer approved by Induced Energy	
Warranty	2 years parts and labour, Ceran top excluded	
CE	Approved	
Pacemakers	Do not operate this equipment if fitted with a pacemaker without consulting your cardiologist	

Induced Energy Limited operates a continuous programme of product development and improvement .Product specifications may therefore be subject to change.

Induced Energy Ltd